package eCH-0051 Arbeitsmodell

Version: 2.8
Ausgabedatum: 14.10.2019
Autor: Patrick Reber, ISC-EJPD

Geschäft

«Informationsobjekt» **businessCaseType**
-caseNumber : string30Type [0..1]

**superType**
«Attr» +Ref-lang : lang [0..1]
«Attr» #Many : anyAttribute
-key : unsignedInt [1]
-sourceID : sourceIDType [0..1]
-alternativeSource : alternativeSourceType [0..*]
-correlationID : sourceIDType [0..1]
-processData : processDataType [0..1]
-descriptionShort : string300Type [0..1]
-description : string4000Type [0..1]
-additionalInformation : string4000Type [0..1]
-file : fileType [0..*]
-openIssue : openIssueType [0..*]
-extension : anyType [0..1]

Person

«Informationsobjekt» **personType**
-address : addressType [0..*]
-meansOfCommunication : meansOfCommunicationType [0..1]

-natural, 1:choice
-legal, 1:choice

**naturalPersonType**
«Attr» #Many : anyAttribute
-dna : yesNoType [0..1]
-foto : yesNoType [0..1]
-daily : yesNoType [0..1]
-swiss Police : yesNo Type [0..1]
-lifeStatus : masterDataType [0..1]
-remark : remarkType [0..*]
-inDossier : yesNoType [0..1]
-checked : process Step Type [0..1]
-established : processStepType [0..1]

**organizationType**
«Attr» #Many : anyAttribute
-currentName : string300Type [1]
-shortName : string20Type [0..1]
-additionalName : string300Type [0..1]
-organizationForm : masterDataType [0..1]
-commercialRegisterNumber : string30Type [0..1]
-foundationDate : datePartiallyKnownType [0..1]
-lineOfBusiness : masterDataType [0..*]

-pastName
0..*

**pastNameType**
-validFrom : dateTimeKnowNType [0..1]
-validTo : dateTimeKnownType [0..1]
-name : string300Type [1]

-identity
0..*

-description
0..*

«Informationsobjekt» **naturalPersonDescriptionType**
-typeOfPersonDescription : masterDataType [0..*]
+Restr» sizeFrom : unsignedShort [0..1]
+Restr» sizeTo : unsignedShort [0..1]
-ageGroupFrom : gYear [0..1]
-ageGroupTo : gYear [0..1]
-typeOfPeople : masterDataType [0..*]
-sex : masterData Type [0..1]
-spoken Words : string4000Type [0..1]
-completion : completionType [0..1]
-ponData : ponData Type [0..1]
-ponZAData : ponZAData Type [0..1]

-characteristic
0..*

**characteristicType**
-type : masterDataType [1]
-value : masterDataType [1]

-bodyCharacteristic
0..*

**bodyCharacteristic**
-part : masterDataType [0..1]
-characteristic : masterDataType [1]
-position : masterDataType [0..1]
-additionalInformation : string4000Type [0..1]

«Informationsobjekt» **naturalPersonIdentityType**
-identityCategory : masterDataType [0..1]
-mainRecord : yesNoType [0..1]
-validFrom : dateTimeKnowNType [0..1]
-validTo : dateTimeKnow nType [0..1]
-officialName : string300Type [1]
-originalName : string300 Type [0..1]
-allianceName : string300Type [0..1]
-alias Name : string300 Type [0..*]
-firstName : string300Type [0..1]
-callName : string300Type [0..1]
-nickName : string300Type [0..*]
-sex : masterData Type [0..1]
-religion : masterData Type [0..1]
-placeOfOrigin : placeType [0..*]
-countryOfOrigin : countryType [0..1]
-cantonOfOrigin : cantonType [0..1]
+Restr» vnNumber : string [0..1]
+Restr» socialSecurityNumber : string [0..1]
-nationality : countryType [0..*]
-profession : string300Type [0..1]
-personalSpecialities : masterDataType [0..*]
-ponData : ponData Type [0..*]
-numberOfChildren : string300Type [0..1]
-oneParentIsCH : yesNo Type [0..1]
-lastNameOfFather : string300Type [0..1]
-firstNameOfFather : string300Type [0..1]
-originalNameOfMother : string300Type [0..1]
-firstNameOfMother : string300Type [0..1]
-spouseIsCH : yesNoType [0..1]
-lastNameOfSpouse : string300Type [0..1]
-firstNameOfSpouse : string300Type [0..1]
-dataOrigin : masterDataType [0..1]
-dataKonsistencyCheck : processStep Type [0..1]
-identificationRemark : remarkType [0..*]
-completion : completion Type [0..1]
-residencePermitCategory : masterDataType [0..1]
-codeName : string50Type [0..1]
-ponZADataWithKey : ponZ4DataWithKeyType [0..*]

-marriageData
0..1

**maritalDataType**
-maritalStatus : masterDataType [1]
-dateOfMaritalStatus : dateTimeKnown Type [0..1]
-separationReason : masterDataType [0..1]
-dateOfSeparation : dateTimeKnown Type [0..1]

-birthData
0..1

-deathData
0..1

**placeDateType**
-date : datePartiallyKnown Type [1]
-country : countryType [0..1]
-place : placeType [0..1]
-municipality : municipalityType [0..1]

-language
0..*

**language Type**
-typeOfLanguage : masterDataType [0..1]
-languageCode : masterDataType [0..1]
-languageIsoCode : languageIsoCodeType [0..1]

Journal

«Informationsobjekt» **journalType**
-journalNumber : string50Type [0..1]
-operationKeyword : masterDataType [0..1]
-excusion : masterDataType [0..1]
-typeOfNotification : masterDataType [0..1]
-actionPlace : addressType [0..1]
-actionPeriodFrom : dateTimeKnowType [0..1]
-actionPeriodTo : dateTimeKnowType [0..1]
-protectionIdentifier : masterDataType [0..1]
-descriptionLong : string64KType [0..1]

Ereignis

-actionPlaceGroup
0..*

**actionPlaceGroupType**
«Attr» #Many : anyAttribute
-key : unsignedInt [1]
-mainRecord : yesNoType [0..1]
-actionPlace : addressType [0..1]
-actionPeriodFrom : dateTimeKnowType [0..1]
-actionPeriodFromApprox Date : yesNoType [0..1]
-actionPeriodFromApprox Time : yesNoType [0..1]
-actionPeriodTo : dateTimeKnow nType [0..1]
-actionPeriodToApproxDate : yesNoType [0..1]
-actionPeriodToApproxTime : yesNoType [0..1]

«Informationsobjekt» **eventType**
-orderAuthority : agencyType [0..1]
-complaintDate : datePartiallyKnownType [0..1]
-attempt : yesNoType [0..1]
-bootyDescription : string4000Type [0..1]
-bootyAmount : amountType [0..1]
-damageToPropertyAmount : amountType [0..1]
-locality : localityType [0..*]
-modeOperandi : masterDataType [0..1]
-actHelpingMeans : masterDataType [0..*]
-facts : string64kType [0..1]
-motive : masterDataType [0..1]
-typeOfCrime : masterDataType [0..1]
-phenomenon : masterDataType [0..*]
-criminalGroup : masterDataType [0..1]
-detailsOnCantonalLaw : masterDataType [0..1]
-remark : remarkType [0..*]

-crimeData
0..*

**crimeDataType**
«Attr» #Many : anyAttribute
-key : unsignedInt [1]
-attempt : yesNoType [1]
-code : masterDataType [0..1]
-additionalInformation : string4000Type [0..1]
-dateOfEntry : dateTimeKnownType [0..1]

-partialSolution
0..*

**partialSolutionType**
«Attr» #Many : anyAttribute
-lvnr : masterDataType [0..1]
-date : dateTimeKnown Type [0..1]
-additionalInformation : string4000Type [0..1]

-NAZInfo
0..1

**NAZType**
-locality type : unsignedInt [1]
-condition : unsignedInt [0..1]
-illustrionDevelopment : unsignedInt [0..1]
-KPOInvolved : yesNoType [0..1]
-EBVBSInvolved : yesNoType [0..1]
-airRotures : yesNoType [0..1]

Ausschreibung

«Informationsobjekt» **alertType**
-type : masterDataType [0..1]
-searchOrder : masterDataType [0..1]
-searchStatus : masterDataType [0..1]
-searchHint : string4000Type [0..1]
-alertHint : string4000Type [0..1]
-disappearDate : dateTimeKnownType [0..1]
-disappearPlace : string300Type [0..1]
-dateOfTheftOrLoss : datePartiallyKnownType [0..1]
-startObservationDate : datePartiallyKnownType [0..1]
-fileReference : string300Type [0..1]
-swissPolice : yesNoType [0..1]
-remark : remarkType [0..*]
-completion : completionType [0..1]

-actionToBeTakenHint
0..*

**flaggedCodeType**
«Attr» #Many : anyAttribute
-flagged : yesNoType [0..1]
-code : masterDataType [1]
-originalCode : masterDataType [0..1]

-flag
0..*

**flagCodeType**
-country : countryType [1]
-code : masterDataType [1]

-areaRestriction
0..1

**areaRestrictionType**
-cantonAbbreviation : cantonAbbreviationType [0..1]
-area : string300Type [0..1]

-notification
0..1

**notificationType**
-typeOfDissemination : masterDataType [1]
-validFrom : dateTimeKnownType [0..1]
-validTo : dateTimeKnown Type [0..1]
-cancellationReason : string300Type [0..1]

-text
1..*

**notificationTextType**
-type : masterDataType [1]
-text : string4000Type [1]

Asservat

«Informationsobjekt» **courtExhibitType**
-type : masterDataType [0..1]
-courtExhibitNumber : string50Type [0..1]
-ponData : ponDataType [0..1]
-adjudication : masterDataType [0..1]
-adjudicationDate : dateTimeKnownType [0..1]
-ponZAData : ponZADataType [0..1]

-storage
0..1

**courtExhibitStorageType**
-typeOfStorage : masterDataType [0..1]
-storageLocality : localityType [1]
-stockNumber : string20Type [0..1]
-shelf : string50Type [0..1]
-cabinet : string50Type [0..1]
-box : string30Type [0..1]
-processData : processStepType [0..1]

-securing
0..1

**courtExhibitSecuringType**
-securingReason : masterDataType [0..1]
-securingLocality : localityType [0..1]
-orderAuthority : agencyType [0..1]
-processData : processStepType [0..1]

-action
0..1

**courtExhibitActionType**
-actionToBeTaken : masterDataType [0..1]
-effectiveAction : masterDataType [0..1]
-typeOfReturn : masterDataType [0..1]
-returnTo : string300 Type [0..1]
-processData : processStepType [0..1]

Fahrzeug

«Informationsobjekt» **vehicleType**
-numberRateCount : unsignedInt
-dataKonsistencyCheck : processStepType [0..1]
-address : addressType [0..1]
-remark : remarkType [0..*]

-numberPlate
0..*

**numberPlateType**
«Attr» #Many : anyAttribute [0..1]
-additionalInformation : string4000Type [0..1]
-number : string30Type [0..1]
-country : countryType [0..1]
-canton : cantonAbbreviationType [0..1]
-typeOfNumber : masterDataType [0..1]
-colour : masterDataType [0..1]
-position : masterDataType [0..1]
-numberPlateStatus : masterDataType [0..1]
-lockCode : masterDataType [0..1]
-dataOrigin : masterDataType [0..1]
-completion : completionType [0..1]
-firstRegistration : dateTimeKnownType [0..1]
-repealDate : dateTimeKnow nType [0..1]
-expirationDate : dateTimeKnownType [0..1]
-retentionDate : dateTimeKnown Type [0..1]
-informationStatus : yesNoType [0..1]

-definition, 0..1

**vehicleDefinitionType**
«Attr» #Many : anyAttribute [0..1]
-vin : string300 Type [0..1]
-vNvCode : masterDataType [0..1]
-usingCode : masterDataType [0..1]
-lockCode : masterDataType [0..1]
-vehicleStatus : masterDataType [0..1]
-mark : masterDataType [0..1]
-modelType : masterDataType [0..1]
-colour : masterDataType [0..1]
-seats : unsignedShort [0..1]
-standingRoom : unsignedShort [0..1]
-engineNumber : string50Type [0..1]
-masterNumber : string50Type [0..1]
-securityNumber : string50Type [0..1]
-typeApproval : string50Type [0..1]
-firstInscription : datePartiallyKnownType [0..1]
-inscription : dateTimeKnownType [0..1]
-exceptTrafficSetting : dateTimeKnownType [0..1]
-lastExamination : dateTimeKnown Type [0..1]
-drivingPower : masterDataType [0..1]
-axles : unsignedShort [0..1]
-typeOfGearbox : masterDataType [0..1]
-generovsNumber : string50Type [0..1]
-capacity : unsignedInt [0..1]
-fuel : masterDataType [0..1]
-derrick : yesNoType [0..1]
-liftingPlatform : yesNoType [0..1]
-ropeHoist : yesNoType [0..1]
-trailerDevice : yesNoType [0..1]
-officialAddition : masterDataType [0..1]
-dataOrigin : masterDataType [0..1]
-completion : completionType [0..1]
-purchaseDate : datePartiallyKnownType [0..1]
-salesDate : datePartiallyKnownType [0..1]
-vehicleValue : amountType [0..1]
-totalWeight : attributeType [0..1]
-tareWeight : attributeType [0..1]
-loadCapacity : attributeType [0..1]
-roofLoad : attributeType [0..1]
-tensileLoad : attributeType [0..1]

-typeOfVehicleGroup
0..*

**typeOfVehicleGroupType**
-typeOfVehicle : masterDataType [1]
-vehicleForm : masterDataType [0..*]

Sache

«Informationsobjekt» **objectType**
-address : addressType [0..1]
-remark : remarkType [0..*]
-completion : completionType [0..1]

-identificationNumber
0..*

**identificationNumberType**
«Attr» #Many : anyAttribute
-mainRecord : yesNoType [0..1]
-isUnique : yesNoType [0..1]
-number : string300Type [1]
-range : string300Type [0..1]
-dataKonsistencyCheck : processStepType [0..1]

-definition, 0..1

**objectDefinitionType**
-typeOfObject : masterDataType [0..1]
-objectStatus : masterDataType [0..1]
-countOfItemsIsUnknown : yesNoType [0..1]
-minItemCount : unsignedInt [0..1]
-maxItemCount : unsignedInt [0..1]
-manufacturer : masterDataType [0..1]
-mark : masterDataType [0..1]
-modelType : masterDataType [0..1]
-country Of Origin : countryType [0..1]
-cantonOfOrigin : cantonType [0..1]
-material : masterDataType [0..*]
-colour : masterDataType [0..*]
-objectDescription : masterDataType [0..*]
-typeOfRealValue : masterDataType [0..1]
-realValue : amountType [0..1]
-workOf : string300Type [0..1]
-saltronOfFirearm : masterDataType [0..*]
-faceValue : amountType [0..*]
-cash : amountType [0..*]
-purchaseDate : datePartiallyKnown Type [0..1]
-salesDate : datePartiallyKnownType [0..1]
-lockCode : masterDataType [0..1]
-lockingAuthority : agencyType [0..1]
-officialAddition : masterDataType [0..*]
-attribute : attributeType [0..*]

-engraving
0..1

**engravingType**
-label : string4000Type [0..1]
-date : dateRefinallyKnow nType [0..1]

-measurement
0..*

**measurementType**
-unitOfMeasurement : masterDataType [1]
-valueFrom : decimal [0..1]
-valueTo : decimal [0..1]

-measurement
0..*

**stoneType**
-typeOfStone : masterDataType [1]
-countOfStonesIsUnknown : yesNoType [0..1]
-mmStoneCount : unsigned int [0..1]
-maxStoneCount : unsigned int [0..1]
-stoneDescription : masterDataType [0..*]
-colour : masterDataType [0..*]

-stone
0..*

-officialDocument
0..1

**officialDocumentType**
«Attr» #Many : anyAttribute
-applicationAuthority : agencyType [0..1]
-applicationNumber : string50Type [0..1]
-applicationDate : dateTimeKnown Type [0..1]
-sequentialDocumentNumber : string50Type [0..1]
-documentInBankNumber : string50Type [0..1]
-issuingAuthority : agencyType [0..1]
-issueDate : dateTimeKnown Type [0..1]
-validTo : dateTimeKnown Type [0..1]
-documentLanguageIsoCode : languageIsoCodeType [0..1]
-validFrom : dateRefinallyKnown Type [0..1]

-permitCategory
0..*

**permitCategoryType**
«Attr» #Many : anyAttribute
-category : masterDataType [0..1]
-examDate : dateTimeKnownType [0..1]
-validTo : dateTimeKnownType [0..1]
-limitation : string50Type [0..1]
-lockCode : masterDataType [0..1]
-lockingAuthority : agencyType [0..1]

Droge

«Informationsobjekt» **drugType**
-typeOfDrug : masterDataType [0..1]
-additive : yesNoType [0..1]
-additiveDescription : string4000Type [0..1]
-gross qQuantity : decimal [0..1]
-typeOfGrossQuantity : masterDataType [0..1]
-netQuantity : decimal [0..1]
-typeOfNetQuantity : masterDataType [0..1]

-minorComponent
0..*
-diluent
0..*

**drugAssayType**
-identity : masterDataType [1]
-description : string4000Type [0..1]
-level : decimal [0..1]
-lesProcedure : masterDataType [0..1]
-lesDate : dateTimeKnownType [0..1]

-majorComponent
0..1

**drugAssayExtendedType**
-gross vWeight : decimal [0..1]
-netWeight : decimal [0..1]
-numberOfSamples : unsignedShort [0..1]
-sampleWeight : decimal [0..1]

Spur

«Informationsobjekt» **traceType**
-typeOfTrace : masterDataType [0..1]
-takenFromPlace : string300Type [0..1]
-attribute : attributeType [0..*]
-ponData : ponDataType [0..1]
-ponZAData : ponZADataType [0..1]

Basistypen

«Union» **dateTimeKnownType**
«Union» **datePartiallyKnownType**
«Restr» **datePartiallyUnknownType**
«Restr» **string4000Type**
«Restr» **string300Type**
«Restr» **string64kType**
«Restr» **string20Type**
«Restr» **string50Type**
«Restr» **cantonAbbreviationType**
«Restr» **countryIsoCodeType**
«Restr» **currencyIsoCodeType**
«Restr» **languageIsoCodeType**
«Restr» **datatypeCodeType**
«Restr» **checksumFunctionType**
«Enum» **yesNoType**

anyAttribute
anyType
anyURI
date
dateTime
gYear
gYearMonth
decimal
unsignedLong
unsignedInt
unsignedShort
string
Namespace xs
lang
Namespace xml

Akte

**fileType**
«Attr» #Many : anyAttribute
-sourceID : sourceIDType [0..1]
-mainRecord : yesNoType [0..1]
-type : masterDataType [0..1]
-versionDate : dateTimeKnownType [0..1]
-versionNumber : string50Type [0..1]
-versioningReason : masterDataType [0..1]
-fileReference : string300Type [0..1]
-additionalInformation : string4000Type [0..1]

-attachment
0..*

**attachmentType**
-filename : string300Type [0..1]
-size : unsignedLong [0..1]
-href : anyURI [0..1]

-checksum
0..1

**checksumType**
«Attr» #checksumFunction : checksumFunctionType [1]

hexBinary

base64Binary

-content
0..1

**binaryContentType**

«Attr»
«Ref»
-contentType
1

**contentType**

**openIssueType**
«Attr» #Many : anyAttribute
-typeOfOpenIssue : masterDataType [0..1]
-recordation : processStepType [0..1]
-subject : markingShortType [0..1]
-message : markingType [0..1]
-dueDate : dateTimeKnownType [0..1]
-startDate : dateTimeKnown Type [0..1]

-openIssue
0..*

**openIssueToType**
«Attr» #Many : anyAttribute
-receiving : processStepType [0..1]
-processing : processStepType [0..*]
-completion : processStepType [0..1]

**pcn24DataWithKeyType**
-key : unsignedInt [1]

**pcn24DataType**
-afaType : masterDataType [0..1]
-date : dateTimeKnown Type [0..1]
-fkKind : masterDataType [0..1]
-fkDate : dateTimeKnown Type [0..1]
-place : placeType [0..1]
-typByname : unsigned int [0..1]
-chainPcn : pcn24Type [0..1]
-firstDailyPcn : pcn24Type [0..1]
-firstDatePcn : pcn24Type [0..1]
-dailyEraseInformation : pcnBaseInformationType [0..1]
-dnaBaseInformation : pcnBaseInformationType [0..1]
-source : string50Type [0..1]
-sourceTable : string50Type [0..1]
«Attr» #Many : anyAttribute

**amountType**
«Attr» #Many : anyAttribute
-amount : decimal [0..1]
-currencyCode : masterDataType [0..1]
-currencyIsoCode : currencyIsoCodeType [0..1]

**simpleValueType**
«Attr» -type : datatypeCodeType [0..1]

-value
1

**attributeType**
«Attr» #Many : anyAttribute
-type : masterDataType [1]
-unit : masterDataType [0..1]
-description : string4000Type [0..1]

**markingType**
«Attr» +Ref» -lang : lang [0..1]

-marking
0..1

**markingShortType**
«Attr» +Ref» -lang : lang [0..1]

-markingShort
0..1

**masterDataType**
«Attr» #Many : anyAttribute
-validFrom : dateTimeKnownType [0..1]
-validTo : dateTimeKnownType [0..1]

**sourceIDType**
«Attr» -source : string50Type [1]
«Attr» -sourceTable : string50Type [1]
«Attr» +version : string20 Type [0..1]
«Attr» -owner : string50Type [0..1]
«Attr» -originalOwner : string50Type [0..1]
«Attr» #Many : anyAttribute

-sourceID
1

-equivalentID
1

**alternativeSourceType**
«Attr» #Many : anyAttribute

**processDataType**
«Attr» #Many : anyAttribute
-nextVerificationDate : dateRefinallyKnownType [0..1]
-expirationDate : dateRefinallyKnownType [0..1]
-decisionDate : datePartiallyKnownType [0..1]
-messageType : masterDataType [0..1]
-confirmationRequest : yesNoType [0..1]

-reporting
0..1
-recordingOffice
0..1
-mutation
0..*
-verification
0..*

**processStepType**
«Attr» #Many : anyAttribute
-date : dateRefinallyKnownType [0..1]
-competentOffice : agencyType [0..1]
-agency : agencyType [0..1]
-responsiblePerson : masterDataType [0..1]
-reason : masterDataType [0..1]
-status : masterDataType [0..1]
-additionalInformation : string4000Type [0..1]

**remarkType**
«Attr» #Many : anyAttribute
-marking : markingType [0..1]
-markingShort : markingShortType [0..1]
-sourceID : sourceIDType [0..1]
-additionalInformation : string4000Type [0..1]

**completionType**
«Attr» #Many : anyAttribute
-typeOfCompletion : masterDataType [0..1]
-completionReason : masterDataType [0..1]
-completionDate : dateTimeKnown Type [0..1]
-investigationPlace : addressType [0..1]
-investigationDate : dateTimeKnown Type [0..1]
-agency : agencyType [0..1]
-responsiblePerson : masterDataType [0..1]
-additionalInformation : string4000Type [0..1]

**pcnDataType**
«Attr» -source : string50Type [0..1]
«Attr» -sourceTable : string50Type [0..1]
«Attr» #Many : anyAttribute
-afaType : masterDataType [0..1]
-date : dateTimeKnown Type [0..1]
«Restr» -pcn : unsignedLong [1]
«Restr» -pcnTz : unsignedInt [1]

Adresse

**addressType**
«Attr» +Ref» -lang : lang [0..1]
-sourceID : sourceIDType [0..1]
-extension : anyType [0..1]
-typeOfAddress : masterDataType [0..1]
-validFrom : dateTimeKnownType [0..1]
-validTo : dateTimeKnown Type [0..1]
-addressLine : string300Type [0..2]
-street : masterData Type [0..1]
-houseNumber : string30Type [0..1]
-houseName : string50Type [0..1]
-level : string20Type [0..1]
-higherDistrict : masterDataType [0..1]
-district : masterDataType [0..1]
-quarter : masterDataType [0..1]
-cityArea : masterDataType [0..1]
-crossingStreet : masterDataType [0..1]
-oppositeSide : yesNoType [0..1]
-additionalInformation : string4000Type [0..1]

-place
0..1

**placeType**
«Attr» #Many : anyAttribute
-marking : markingType [0..1]
-sourceID : sourceIDType [0..1]
-zipCode : string20Type [0..1]

-canton
0..1

**cantonType**
«Attr» #Many : anyAttribute
-marking : markingType [0..1]
-sourceID : sourceIDType [0..1]
-cantonAbbreviation : cantonAbbreviationType [0..1]

-country
0..1

**countryType**
«Attr» #Many : anyAttribute
-marking : string4000Type [0..1]
-sourceID : sourceIDType [0..1]
-validFrom : dateTimeKnownType [0..1]
-validTo : dateTimeKnownType [0..1]
-countryIsoCode : countryIsoCodeType [0..1]
-nationID : unsigned int [0..1]

-municipality
0..1

**municipalityType**
«Attr» #Many : anyAttribute
-marking : markingType [0..1]
-sourceID : sourceIDType [0..1]
-municipalityID : unsigned int [0..1]

-coordinate
0..1

**coordinateType**
«Attr» #Many : anyAttribute
-northSouth : decimal [1]
-eastWest : decimal [1]

-locality
0..*

**localityType**
«Attr» #Many : anyAttribute
-localityCode : masterDataType [1]
-additionalInformation : string4000Type [0..1]

-roadOutOfType
0..*

**roadOutOfType**
«Attr» #Many : anyAttribute
-typeOfRoadOut : masterDataType [0..1]
-name : string300Type [0..1]
-number : string50Type [0..1]
-direction : string300Type [0..1]
-speedLimit : unsigned int [0..1]
-additionalInformation : string4000Type [0..1]

Kommunikationsmittel

**meansOfCommunicationType**

-telephone
0..*
-fax
0..*
-page
0..*

**telephoneType**
«Restr» +phoneNumberInternational : string [1:choice]
«Restr» +phoneNumberSwiss : string [1:choice]

**communicationType**
-sourceID : sourceIDType [0..1]
-extension : anyType [0..1]
-typeOfConnection : masterDataType [0..1]
-usage : masterDataType [0..1]
-preferred : yesNoType [0..1]
-subscriber : yesNoType [0..1]
-keepUnderSurveillance : yesNoType [0..1]
-validFrom : dateTimeKnownType [0..1]
-validTo : dateTimeKnownType [0..1]
-provider : masterDataType [0..1]
-country : countryType [0..1]
-place : placeType [0..1]
-homepage : string4000Type [0..1]
-status : masterDataType [0..1]

-mobile
0..*

**mobileType**
-isEnabled : yesNoType [0..1]
-localNumber : string20Type [0..1]
-imsiNumber : string20Type [0..1]
-imeiNumber : string20Type [0..1]
-msisdnNumber : string20Type [0..1]

-eMail
0..*

**eMailType**
-eMailAddress : string300Type [1]

-url
0..*

**urlType**
-url : string4000Type [1]

-other
0..*

Dokument

**documentType**
«Attr» +Ref» -lang : lang [1]
«Attr» -anyAttribute
-person : personType [0..*]
-vehicle : vehicleType [0..*]
-object : objectType [0..*]
-drug : drugType [0..*]
-trace : traceType [0..*]
-courtExhibit : courtExhibitType [0..*]
-journal : journalType [0..*]
-event : eventType [0..*]
-alert : alertType [0..*]
-businessCase : businessCaseType [0..*]

-processData
0..1

**globalProcessData**
«Attr» #Many : anyAttribute
-deliveryDate : dateTimeKnownType [0..1]
-sender : processStep Type [0..1]
-recipient : processStepType [0..*]
-sourceID : sourceIDType [0..1]
-correlationID : sourceIDType [0..1]
-processing Status : masterDataType [0..1]
«Restr» -schemaVersion : string [0..1]
-interfaceVersion : string30Type [0..1]
-softwareVendor : string300Type [0..1]
-softwareProduct : string300Type [0..1]
-softwareVersion : string300Type [0..1]
-messageType : masterDataType [0..1]

-relations
0..1*

**relationsType**
-businessCaseLink : masterSlaveLinkType [0..*choice]
-personLink : masterSlaveLinkType [0..*choice]
-involvedParty : involvedPartyType [0..*choice]
-adjudication : adjudicationType [0..*choice]
-financialTransaction : financialTransactionType [0..*choice]
-hearingOfEvidence : hearingOfEvidenceType [0..*choice]
-mediaSupply : mediaSupplyType [0..*choice]
-sentenceDemanded : sentenceDemandedType [0..*choice]
-publicEvent : publicEventType [0..1 choice]
-eventBusinessCaseLink : eventBusinessCaseLinkType [0..*choice]
-eventJournalLink : eventJournalLinkType [0..*choice]
-eventVehicleLink : eventVehicleLinkType [0..*choice]
-eventObjectLink : eventObjectLinkType [0..*choice]
-eventDrugLink : eventDrugLinkType [0..*choice]
-eventTraceLink : eventTraceLinkType [0..*choice]
-alertObjectLink : alertObjectLinkType [0..*choice]
-alertVehicleLink : alertVehicleLinkType [0..*choice]
-journalLink : masterSlaveLinkType [0..*choice]
-journalObjectLink : journalObjectLinkType [0..*choice]
-journalPersonLink : journalPersonLinkType [0..*choice]
-journalVehicleLink : journalVehicleLinkType [0..*choice]
-objectLink : masterSlaveLinkType [0..*choice]
-objectPersonLink : objectPersonLinkType [0..*choice]
-vehicleLink : masterSlaveLinkType [0..*choice]
-vehiclePersonLink : vehiclePersonLinkType [0..*choice]
-drugPersonLink : drugPersonLinkType [0..*choice]
-traceLink : masterSlaveLinkType [0..*choice]
-tracePersonLink : tracePersonLinkType [0..*choice]
-courtExhibitBusinessCaseLink : courtExhibitBusinessCaseLinkType [0..*choice]
-courtExhibitLink : masterSlaveLinkType [0..*choice]
-courtExhibitVehicleLink : courtExhibitVehicleLinkType [0..1 choice]
-courtExhibitObjectLink : courtExhibitObjectLinkType [0..*choice]
-courtExhibitDrugLink : courtExhibitDrugLinkType [0..*choice]
-courtExhibitTraceLink : courtExhibitTraceLinkType [0..*choice]